


# GeoSwath 4 PHS

GeoSwath 4 Portable Hydrographic System (PHS)



GeoAcoustics

## OVERVIEW

Designed for rapid deployment on diverse vessels of opportunity including RIBS, the GeoSwath PHS is the most efficient turnkey solution for simultaneous swath bathymetry and side scan seabed mapping in shallow waters. As a complete package, it includes:

### GeoSwath 4R

The GeoSwath system is available in 125 kHz, 250 kHz and 500 kHz frequencies, with each frequency determining the maximum depth of operation, depth resolution and maximum swath width.

### Applanix POS MV SurfMaster

This GNSS aided inertial navigation system consists three main components; POS Computer System (PCS), Inertial Measurement Unit (IMU) fitted to the GeoSwath transducer head, and two GNSS antennas. It allows for higher immunity to GNSS outages in areas of problematic satellite reception, such as ports, harbours, rivers, near-shore coastal waters and near offshore structures, and is Supplied with 6 months subscription to POSpac Go! PP-RTX.

### Valeport Sound Velocity Sensors (SVS)

The SVS is attached to the transducer head and connected directly to the GeoSwath 4R. Further, a Valeport Swift Sound Velocity Profiler (SVP) is part of the PHS system, enabling SV dips during the survey. This data is easily incorporated into the GeoSwath software package during processing.



### Over the Side Mount

The GeoAcoustics OTS mount is a rugged, tried and tested design which is simple to operate and install. A sectional mounting pole is supplied allowing different freeboards to be accommodated. At the top of the pole 2 GNSS antennas are fixed with a 1.9 m baseline separation which are in turn connected to the PCS.

### GS4 Software and PC

A Panasonic Toughbook is supplied as part of the PHS which includes a pre-configured installation of the GS4 software. It provides a complete project-based solution; acquisition, storing and editing of sonar and ancillary data, grid-based patch test calibration, data processing, advanced bathymetry data gridding, side scan mosaicing and 3-D data visualisation.



GeoAcoustics

# GeoSwath PHS Technical Specifications

| GeoSwath 4 Transducer                                  | 125 kHz  | 250 kHz   | 500 kHz   |
|--|--|---|---|
| Max Water Depth Below Transducers                      | 200 m  | 100 m   | 50 m  |
| Max Swath Width  | 780 m  | 390 m   | 190 m   |
| Max Coverage   | Up to 12 x depth   | Up to 12 x depth                                | Up to 12 x depth                                |
| Range Resolution                                       | 6 mm   | 3 mm  | 1.5 mm  |
| Angular Resolution                                     | 0.04°  | 0.04°   | 0.04°   |
| Two-Way Beam Width (Horizontal)                        | 0.85°  | 0.75°   | 0.5°  |
| Max Swath Update Rate                                  | 30 per second (simultaneous port and starboard)  | 30 per second (simultaneous port and starboard) | 30 per second (simultaneous port and starboard) |
| Transducer Head Dimensions                             | 550 mm (L) x 250 mm (W) x 190 mm (H)   | 468 mm (L) x 165 mm (W) x 125 mm (H)            | 362 mm (L) x 109 mm (W) x 75 mm (H)             |
| Transducer Head Weight, including peripherals (approx) | 35 kg  | 20 kg   | 14 kg   |
| Over the Side Mount                                    | Deck Mount Assembly: 1410 mm (L) x 152 mm (W) x 337 mm (H) (24 kg)<br>Each Pole (x3): 1829 mm x 70 mm OD (11 kg) |   |   |

## GeoSwath 4R Deck Unit

|             |   |
|-------------|---|
| Physical    | Dimensions: 440 mm (D) with connectors x 342 mm (W) x 136 mm (H)   Weight: 12.5 kg  |
| Power       | 18-26 VDC, 60 W peak power  |
| Environment | 0 °C to 40 °C, -20 °C to 70 °C (storage)   < 95 % RH non-condensing (operation), < 55 % RH non-condensing (storage)   IP66 rated ingress protection |
| Interface   | Laptop via ethernet   |

## POS MV SurfMaster

|               |   |
|---------------|---|
| Physical      | Dimensions: 167 mm (D) x 356 mm (W) x 68 mm (H)   Weight: 2.5 kg  |
| Power         | 10-34 VDC, 35 W peak power  |
| Position Acc. | DPGS 0.5-2 m depending on quality of differential corrections   POSpac PPP Horizontal <0.1 m, Vertical <0.2 m |
| Heading Acc.  | 0.08° with 2 m baseline   |
| Heave         | 5 cm or 5 %. Whichever is greater, for periods of 14 s or less  |

## Valeport SVS / SVP

|                               |   |
|-------------------------------|---|
| Sound Velocity Sensor (SVS)   | Range 1375-1900 m/s. Resolution 0.001 m   |
| Sound Velocity Profiler (SVP) | (Swift) Range 1375-1900 m/s. Resolution 0.001 m, Accuracy +/- 0.02 m/s   Weight: 2 kg (air), 0.9 kg (water) |

Specifications subject to change without notice. E&OE